





FH300RC TWIN HEAD

Iss 2. Metal Halide / UV Glass Remote Control Variable Speed





APPLICATION

The FRANCIS TWIN HEAD Range of Remote Control searchlights has been designed with the precise aim of bringing to the market, the ultimate searchlight for both navigation and search and rescue.

The FH300RC has two light sources within the twin headed design, one white light and the other UV light, therefore able to identify oil spill hazards.

The quality and design of structure has been carefully developed to withstand the extraordinary conditions while in use in the harshest of environment, such as Coast Guard patrol. The heavy duty variable speed gearbox is strong, powerful and able to operate in the rough seas and high strength winds as found in coastal areas throughout the world.

These units are particularly suitable for use on patrol Craft, custom vessels and is used extensively in security applications.

The metal halide offers a colour temperature of 6000k similar to daylight, and offers exceptional illumination, especially in polar regions and long range navigation.

SPECIFICATION

- Instant re-strike. No "cooling" down time required.
- Toughened super clear Optiwhite front glass.
- Parabolic glass reflector.
- Constructed from marine grade materials and fixings.
- Powder coated and stove enamel paint finish.
- Pan rotation 385°.
- Tilt elevation control +45°, -45°.
- Variable Rotation Speed 1 to 20°/sec (Pan).
- Variable Elevation Speed 1 to 10°/sec (Tilt).
- Heater fitted in gearbox & barrel standard.
- Operational temp -50°.
- Remote lamp focus, 2.5° spot to 10° flood.
- High quality PSU 50/60 Hz 1ph.
- Sealing IP66 Gearbox, IP56 Searchlight, PSU IP66.
- Searchlight weight 75kgs.
- PSU weight 9.5kgs. each.

ALL DIMENSIONS IN MILLIMETRES

Base fixing details:

4 holes 12.5 Ø equi-spaced on a 350mm PCD Joystick panel 205 x 150mm

PSU dimensions: 280 x 190 x 182mm (each)

Part Numbers

Type Supply Watts Part No FH300RC 230v 575w A6074 575w G22 Lamp D15764 Optional Additional UV glass Assembly

VAC	Lamp life	Range @ 1 Lux	PBCP X 1000	Div	Watts
230v	1000 hrs	3685m	13,600	2.5°	575w

For	more	information	contact:

Francis Searchlights Limited
Union Road, Bolton, BL2 2HJ, UK
Tel 44 (0) 1204 558960 Fax 44 (0) 1204 558979
Email sales@francis.co.uk Web site www.francis.co.uk