





LH230 Issue 2 Metal Halide 150w Architectural



FRONT VIEW



APPLICATION

This new Francis luminaire is an ideal substitute where floodlights are unable to provide the throw required to highlight certain architectural features.

Whether to be used as an uplight or downlight, this product has many uses in the illumination of buildings, statues, spires and garden features.

These are also available for use with this 150w version of lower 70w lamp. The unit can also be used in conjunction with a reeded glass in order to collimate the light, thus providing a uniform floodlit effect.

This new development provides a 300% increase in performance over the previous model offered and is easily maintained, having removable spill rings and ease of lamp replacement.

PART NUMBERS

Туре	Supply	Part Number
LH230 Searchlight	240v	A2918
Control Gear Assy	240v	C23515-00

SPECIFICATION

- Constructed from 304 stainless steel. Standard paint finish
- Is satin black.
- Parabolic formed deep dish aluminium reflector.
- Powder coated finish.
- External lamp focus adjustment.
- Toughened front glass.
- Spill rings to prevent unwanted glare & stray light.
- Axially mounted Metal Halide light source.
- Sealing to IP66.
- Supplied with stainless steel security bracket and safety cable.

Performance Data

	Lamp Life hrs	PBCP	Divergence	Lamp Part Number
150w	12 000	1 024 763	4° to 8°	D16817

Francis Searchlights Limited Union Road, Bolton, BL2 2HJ, UK Tel 44 (0) 1204 558960 Fax 44 (0) 1204 558979 Email sales@francis.co.uk Web site www.francis.co.uk

Weight	
LH230	8.40 Kg
Control Gear Assy	0.40 Kg

Fixing Details

2 holes Ø12.50mm at 70mm centres

Useful Information (based on divergence at 5°)

At 25m, provides beam diameter of 2.18m @ 1639 lux At 50m, provides beam diameter of 4.36m @ 409 lux At 100m, provides beam diameter of 8.73m @ 102 lux

Range to 1 lux is 1012m

For more information please contact your local Agent/Distributor: